

AD-A083 299

ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND ABERD--ETC F/8 19/1
SIMPLIFIED DETERMINATION OF RETARDATION FOR KINETIC ENERGY PROJ--ETC(U)
FEB 80 U F DONOVAN

UNCLASSIFIED


ARSL-MR-02994

SBIE -AD-E430 399

NL

[unc]
AD-A083 299





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

ADA 083299

(12) *NW* **LEVEL III**

AD-E 430 399

AD

MEMORANDUM REPORT ARBRL-MR-02994

SIMPLIFIED DETERMINATION OF RETARDATION
FOR KINETIC ENERGY PROJECTILES

William F. Donovan

February 1980

DTIC
ELECTE
APR 22 1980
S B D



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

80 4 4 002

DDC FILE COPY

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22151.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute endorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR-02994	2. GOVT ACCESSION NO. A083 299	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) SIMPLIFIED DETERMINATION OF RETARDATION FOR KINETIC ENERGY PROJECTILES	5. TYPE OF REPORT & PERIOD COVERED	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) WILLIAM F. DONOVAN	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Ballistic Research Laboratory ATTN: DRDAR-BLP Aberdeen Proving Ground, MD 21005	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L162618AH80	
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Armament Research & Development Command U.S. Army Ballistic Research Laboratory ATTN: DRDAR-BL Aberdeen Proving Ground, MD 21005	12. REPORT DATE FEBRUARY 1980	
	13. NUMBER OF PAGES 26	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
15a. DECLASSIFICATION/DOWNGRADING SCHEDULE		
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release, distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Drag Coefficient KE Projectile Retardation C _d		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) jmk Correspondence between experimental and analytical determinations of retardation is demonstrated for a particular flight projectile. The predictive model requires only the projectile physical dimensions and mass and presumes a linear drag coefficient characteristic.		

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS.	5
LIST OF SYMBOLS.	7
I. INTRODUCTION	9
II. PROCEDURE.	9
III. RESULTS AND CONCLUSIONS.	11
REFERENCES	17
APPENDIX A	19
APPENDIX B	21
APPENDIX C	23
DISTRIBUTION LIST.	25

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION _____	
BY _____	
DISTRIBUTION/AVAILABILITY CODES	
Dist	Ac. and/or SPECIAL
A	

LIST OF ILLUSTRATIONS

Figure	Page
1-a Outline of XM110 Projectile.	12
1-b Outline of Idealized Model	13
2 Drag Coefficient Characteristics	14
3-a Velocity vs Range for $M_0 = 4.24$	15
3-b Velocity vs Range for $M_0 = 4.06$	16

PRECEDING PAGE NOT FILMED
BLANK

LIST OF SYMBOLS

A	reference area, $\frac{\pi d^2}{4}$
A _{form}	fin form area
A _{sect}	sectional area of fin, t h
A _{wet}	wetted area
C _D	drag coefficient, $\frac{\text{Drag Force}}{\frac{1}{2} \rho v^2 A}$
F	drag force
M	mach number
N	number of fin blades
Q	operational parameter, $\frac{\rho A b}{2 m}$
R	operational parameter, $\frac{k M_o + b}{M_o}$
a	acceleration of projectile, $\frac{dv}{dt}$
b	intercept of C _D vs M characteristic
c _r	length of fin blade at root
d	reference diameter, 1.0 cal
h	height of fin blade
j	length of fin blade leading edge
k	slope of C _D vs M characteristic
l _a	length of body
l _n	length of nose
l _{o.a.}	overall length of projectile
l _T	length of forebody, l _a + l _n
m	mass of projectile

LIST OF SYMBOLS (Cont'd)

s	distance along trajectory
\dot{s}	differentiation of s with respect to time
t	thickness of fin blade
v	velocity of projectile, $\frac{ds}{dt}$
\dot{v}	differentiation of velocity with respect to time
ρ	density of air

Subscripts

0	conditions at gun muzzle
1	conditions along trajectory

I. INTRODUCTION

Long rod kinetic energy penetrators often find tactical application in the particular aerodynamic environment of normal temperature and pressure and flat fire trajectory. This follows from the requirement of very high velocity, which implies a short time of flight and small gravity drop, and from the fact that the many tank battlefields of the world are at nominal sea-level altitudes. This circumstance permits some simplification to the calculation of the trajectory of proposed projectiles still in the preliminary stages of design and analysis. For preliminary design purposes, the Mach number excursion can be considered very short and the drag coefficient over the range of flight can be considered linear. The retardation then appears in closed form solution whereby, given the drag coefficient characteristic, the velocity becomes an explicit function of range.

II. PROCEDURE

In the free flight regime, the force balance along the axis of the zero yaw trajectory gives¹

$$\begin{aligned} F &= m \dot{v} \\ &= - \frac{1}{2} \rho v^2 A C_D \end{aligned} \quad (1)$$

where

F = axial force opposing the acceleration of the projectile,

\dot{v} = the acceleration of the projectile,

ρ = the density of the flight medium,

v = velocity of the projectile,

A = reference area, and

C_D = drag coefficient.

The differential expression becomes

$$\frac{dv}{v} = - \frac{\rho A C_D}{2 m} ds \quad (2)$$

¹C. H. Murphy, "Free Flight Motion of Symmetric Missiles", BRL Report No. 1216, July 1963, (AD #442757).

where

$$\dot{v} = \frac{dv}{dt} ,$$

$$v = \frac{ds}{dt} , \text{ and}$$

s = distance along trajectory.

With

$$C_D = k M + b ,$$

where

b = intercept of C_D vs M characteristic,

k = slope of C_D vs M characteristic, and

$$\frac{dv}{v} = - \frac{1}{2} \frac{\rho}{m} A (k M + b) ds = \frac{dM}{M} , \text{ since } M \text{ is proportional to } v ,$$

or

$$\frac{dM}{M} = - \frac{1}{2} \frac{\rho}{m} A (k M + b) ds .$$

Upon integration (Appendix A) ,

$$M = \frac{b}{R e^{Qs} - k} , \tag{3}$$

where

M = Mach number along trajectory,

s = distance along trajectory ,

$$R = \frac{k M_o + b}{M_o} ,$$

M_o = Mach number at muzzle, and

$$Q = \frac{\rho A b}{2 m} .$$

With "s" the argument, M can be determined directly. This equation is presented in HP-97 program formulation in Appendix B.

An example will illustrate the application. Figure 1-a is an outline of a typical long rod penetrator (flechette) for which range data and measured retardation to 600 meters are available². Figure 1-b shows an idealized model of this projectile with a simple fin. The corresponding experimental and calculated³ drag coefficients are presented in Figure 2 where the range values represent turbulent flow conditions for small yaw flight. The viscous contribution to the calculated curve assumes turbulent flow friction factors but is posed for zero yaw and presumes a linear drag characteristic.


III. RESULTS AND CONCLUSIONS

In Reference 2, the experimental range velocities are presented to 600 meters (335,000 cal) with extrapolation to 1000 meters (536,102 cal). These data are transposed and values based on the linearized characteristic and Eq. (3) via Appendix A are given on Figure 3a and 3b for $M_o = 4.24$ and $M_o = 4.06$ respectively. The maximum deviation is within 3% over the full range.

Although discrete measurements for similar projectiles are not available for comparison, similar agreement may be expected.

²Maynard Piddington, "The Aerodynamic Characteristics of a SPIW Projectile", BRL Memorandum Report 1594, September 1964. (AD #355679)

³William F. Donovan and Bertram B. Grollman, "Procedure for Estimating Zero Yaw Drag Coefficients for Long Rod Projectiles at Mach Numbers from 2 to 5", ARBRL MR 02819, March 1978. (AD #A054326)





WT.	115	CAL ³
I _x		CAL ⁵
I _y	2452	CAL ⁵
DIA	1.0	CAL
P	7.86	

Figure 1-a. Outline of XM110 Projectile

SOURCE: Reference 2

* CALIBER NOMENCLATURE discussed in APPENDIX C



WT.	115	CAL ³
I _x		CAL ⁵
I _y	2452	CAL ⁵
DIA	1.0	CAL
P	7.86	

Figure 1-b. Outline of Idealized Model

* CALIBER NOMENCLATURE discussed in APPENDIX C




Figure 2. Drag Coefficient Characteristics




Figure 3-a. Velocity vs Range for $M_0 = 4.24$




Figure 3-b. Velocity vs Range for $M_0 = 4.06$

REFERENCES

1. C. H. Murphy, "Free Flight Motion of Symmetric Missiles", BRL Report No. 1216, July 1963, (AD #442757).
2. Maynard Piddington, "The Aerodynamic Characteristics of a SPIW Projectile", BRL Memorandum Report 1594, September 1964. (AD #355679)
3. William F. Donovan and Bertram B. Grollman, "Procedure for Estimating Zero Yaw Drag Coefficients for Long Rod Projectiles at Mach Numbers from 2 to 5", ARBRL MR 02819, March 1978. (AD #A054326)

APPENDIX A

INTEGRATION SUMMARY OF EQUATION (3)

From Equation (2)

$$\begin{aligned}\frac{dv}{v} &= - \frac{1}{2m} \rho A C_D ds \\ &= - \frac{1}{2m} \rho A (kM + b) ds,\end{aligned}$$

$$\frac{dM}{M(kM + b)} = - \frac{1}{2m} \rho A ds,$$

and #34 in Pierce's Table of Integrals* gives

$$- \frac{1}{b} \left[\ln \frac{kM + b}{M} \right]_{M_1}^{M_0} = - \left[\frac{\rho A s}{2m} \right]_{s_1}^{s_0}$$

which is easily verified by differentiation.

Then


$$\frac{\frac{kM_0 + b}{M_0}}{\frac{kM_1 + b}{M_1}} = e^{-\frac{\rho A s_1 b}{2m}}$$

for $s_0 = 0$.

By transposition and substitution

*R.O. Pierce, A Short Table of Integrals, Ginn and Company, Boston, 1929.

This integration form was independently presented by Mr. James Bradley of LFD.



$$\frac{k M_o + b}{M_o} e^{\frac{\rho A b s_1}{2 m}} = \frac{k M_1 + b}{M_1} ,$$

$$R e^{Qs_1} = \frac{k M_1 + b}{M_1} , \text{ and}$$

$$M_1 = \frac{b}{R e^{Qs_1} - k} .$$

APPENDIX B

H-P PROGRAM FOR RETARDATION

This program requires the physicals of the projectile and the linear approximation of the C_D vs M curve. It includes a stepping feature within a loop which automatically decrements the range and repeats the calculation. The input is dimensioned in the units in common usage locally.

Input

R₁ Extreme range in meters
 R₂ Initial Mach number
 R₃ Shaft diameter in inches
 R₄ Projectile weight in pounds
 R₅ Intercept of C_D vs M curve
 R₆ Slope of C_D vs M curve
 R₇ Conversion constant = .000671
 R₈ Range decrement

Output

Range in meters
 Initial Mach number
 Mach number at specified range
 Retardation in ft/sec/km

001	*LBLE	21 15	019	RCL7	36 07	037	CHS	-22
002	RCL1	36 01	020	x	-35	038	RCL2	36 02
003	X=0?	16-43	021	RCL5	36 05	039	+	-55
004	RTN	24	022	x	-35	040	1	01
005	PRTX	-14	023	RCL4	36 04	041	1	01
006	CLX	-51	024	÷	-24	042	2	02
007	RCL2	36 02	025	RCL1	36 01	043	0	00
008	PRTX	-14	026	x	-35	044	0	00
009	RCL6	36 06	027	e ^x	33	045	0	00
010	x	-35	028	RCLA	36 11	046	0	00
011	RCL5	36 05	029	x	-35	047	x	-35
012	+	-55	030	RCL6	36 06	048	RCL1	36 01
013	RCL2	36 02	031	-	-45	049	÷	-24
014	÷	-24	032	RCL5	36 05	050	PRTX	-14
015	STO0	35 11	033	+	-24	051	SPC	16-11
016	CLX	-51	034	1/X	52	052	RCL1	36 01
017	RCL3	36 03	035	PRTX	-14	053	RCL8	36 08
018	X*	53	036	STO0	35 12	054	-	-45
						055	STO1	35 01
						056	GT0E	22 15
						057	RTN	24
						058	R/S	51

APPENDIX C

CALIBER NOMENCLATURE

Caliber nomenclature is widely used in aerodynamic expression as a dimensional convenience to compare performance parameters of geometrically similar models. It is usually referred to a linear scale representing the arithmetic ratio of a linear dimension to an arbitrary standard - most often the body diameter at the forward bourrelet - but has been employed to identify volumes*. Only a simple extension of the reasoning is required then to simultaneously de-dimensionalize the "mass" factor in a given expression and deduce a normalized system of mechanical units which permits a rational comparison of the dynamic properties of even geometrically dissimilar elements of machinery. Usually the context of discussion identifies the quantities as "mass cal", "inertia cal" "length cal", etc., although a complete lexicon of explicit and descriptive terms is available for this purpose.

For this report, the following correlation is employed:

$$\text{Length (cal)} = \frac{\text{linear dimension}}{\text{diametral dimension}}$$

$$\text{Weight (cal}^3) = \frac{\text{gravity weight}}{\text{gravity weight of unit volume of water}}$$

$$= \text{S.G.}$$

$$\text{Mass (cal}^2 \text{ sec}^2) = \frac{\text{S.G.}}{\text{gravity acceleration}}$$

Thus, with force equal to mass times acceleration:

$$(\text{cal}^3) = (\text{cal}^2 \text{ sec}^2) \left(\frac{\text{cal}}{\text{sec}^2} \right)$$

*MacAllister, et al., "A Compendium of Ballistic Properties of Projectiles of Possible Interest in Small Arms", BRL Report No. 1532, February 1971, (AD #882117).

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Documentation Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	6	Commander US Army Armament Research and Development Command ATTN: DRDAR-SC, Dr. D. Gyorog Mr. S. Jacobson DRDAR-SCT, Dr. T. Hung DRDAR-LCA, Mr. R. Wrenn Mr. A. Loeb Mr. S. Wasserman Dover, NJ 07801
1	Director Defense Advanced Research Projects Agency ATTN: Mr. G. Ligman, Jr. 1400 Wilson Boulevard Arlington, VA 22209	1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299
1	Director Institute for Defense Analyses ATTN: Dr. H. Wolfhard 400 Army Navy Drive Arlington, VA 22202	1	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Watervliet, NY 12189
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333	2	Commander US Army Watervliet Arsenal ATTN: SARWV-RDD, P. Vottis DRDAR-LCB, Mr. T. Allen Watervliet, NY 12189
5	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCS-T MAJ J. Houle (3 cys) DRDAR-TSS (2 cys) Dover, NJ 07801	1	Commander US Army Aviation Research and Development Command ATTN: DRSAR-E 12th and Spruce Streets St. Louis, MO 63166
6	Commander US Army Armament Research and Development Command ATTN: DRDAR-LC, Dr. J. Frasier DRDAR-LCA Mr. W. Benson Dr. H. Fair DRDAR-LCU, Mr. A. Moss Mr. D. Davitt Mr. D. Costa Dover, NJ 07801	1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Communications Rsch and Development Command ATTN: DRDCO-PPA-SA Fort Monmouth, NJ 07703	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL, Tech Lib White Sands Missile Range NM 88002
1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703	2	Commandant US Army Artillery & Missile School ATTN: AKPSIAS-G-CN AKPSIAS-G-RK Fort Sill, OK 73504
2	Commander US Army Missile Command ATTN: DRDMI-YDL DRDMI-R Redstone Arsenal, AL 35809	1	Chief of Naval Research ATTN: Code 473 800 N. Quincy Street Arlington, VA 22217
1	Commander US Army Tank Automotive Research & Development Cmd ATTN: DRDTA-UL Warren, MI 48090	2	Commander Naval Surface Weapons Center ATTN: Tech Lib, Dr. L.L.Pater Dahlgren, VA 22448
1	Commander US Army White Sands Missile Range ATTN: STEWS-VT White Sands, NM 88002	1	Commander Naval Research Laboratory ATTN: Code 6180 Washington, DC 20375
1	Project Manager, XM1 US Army Tank Automotive Research & Development Cmd 28150 Dequindre Road Warren, MI 48090	1	Commander Naval Ordnance Station ATTN: Dr. A. Roberts Indian Head, MD 20640
1	Commander US Army Research Office ATTN: Tech Lib P. O. Box 12211 Research Triangle Park, NC 27706		<u>Aberdeen Proving Ground</u> Dir, USAMSAA ATTN: DRXSY-D DRXSY-MP, H. Cohen Cdr, USATECOM ATTN: DRSTE-TO-F Dir, Wpns Sys Concepts Team, Bldg. E3516, EA ATTN: DRDAR-ACW

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet and return it to Director, US Army Ballistic Research Laboratory, ARRADCOM, ATTN: DRDAR-TSB, Aberdeen Proving Ground, Maryland 21005. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____
2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

